



SNP100-24VFP-1

SELV. Short circuit, overload and over heat protection. Compliance to CLASS II , lifetime 30,000hrs.



Items	Conditions	Request	Note
Input voltage	Ta	200-240Vac	--
Input frequency		50/60Hz	--
Input current	25℃, rated input voltage, output with max. rated power	<0.7A	--
Input power		<118W	--
Efficiency		≥90%	--
Standby	25℃, rated input voltage, output without load	<0.5W	average
Inrush current	25℃, rated input voltage	<75A	peak
PF	25℃, rated input voltage, output max. rated power	≥ 0.9	--

Item	Conditions	Request	Note
Operation temp.	--	-20-50℃	--
Relative humidity	--	45%-85%	--
Max. case temp.	--	85℃	--
Lifetime	Max.Ta, rated input voltage, output with max.rated power	30,000hr	--
Working noise	25℃, rated input voltage, output with rated power, mute box background noise<35dB, pickup 10cm distance from products	yes	--

Items	Conditions	Request	Note
Open circuit	Ta, rated input voltage, no load	--	--
Over load	Ta, 0.94-1.06 times of input voltage, 1.6 times of rated power	Yes	--
Short circuit	Ta, 0.94-1.06 times of input voltage	Yes	--
Over temperature	Ta, 0.94-1.06 times of input voltage, temperature detected pointed more than 115 degree	Yes	--
Over voltage	Ta, 0.94-1.06 times of input voltage, output voltage is 1.5 times of rated one	Yes	--
Auto recovery	Over load, short circuit revocation	Yes	--
Latch off	Over heat re-start after cut off	Yes	--

Items	Conditions	Request	Note
Startup time	25℃, rated input voltage, output with max. rated power	<0.5S	--
Output voltage and precision	Ta, rated input voltage, output with rated power	24V±5%	--
Output current range	Ta, rated input voltage	0-4.17A	
Output voltage wave	25℃, rated input voltage, output with max. rated power	600mV	Vp-p
Output overload	25℃, rated input voltage, output with 2 times LED load	Yes	--
Output current and precision	Ta, rated input voltage, output with rated power	--	--
Rated output voltage range	Ta, rated input voltage	--	--
Output current wave	25℃, rated input voltage, output with max. rated power	--	Ip-p
Dimming mode	--	--	--
Dimming range	--	--	--

Items	Conditions
Case material and size	Plastic Case 356x30x20mm
Mounting ways	Independent
Insulation type	Class II
IP grade	IP66
Input cables dimension	H05RN-F 2*1.0mm ²
Output cables dimension	SVT 18AWGX2C
Output cables length	--

Items	Conditions
Safety	IEC61347-1, IEC61347-2-13
Harmonic	EN61000-3-2 Class C
EMI	EN55015
EMS	EN61000-4-2, 3, 4, 5, 6 EN61547

● Dimensions(mm)

