



LED POWER SUPPLY DATASHEET

SNP60-24VFP-1

·DESCRIPTION

SELV. Open circuit, short circuit, overload and over heat protection. Compliance to CLASS II, lifetime 30,000hrs.

·Input

Items	Conditions	Request	Note
Input voltage	Ta	180-264Vac	--
Input frequency		50/60Hz	--
Input current	25°C, rated input voltage, output with max. rated power	<0.5A	--
Input power		<75W	--
Efficiency		≥88%	--
Standby	25°C, rated input voltage, output without load	<0.5W	average
Inrush current	25°C, rated input voltage	<75A	peak
PF	25°C, rated input voltage, output max. rated power	≥0.90	--

·Output

Items	Conditions	Request	Note
Startup time	25°C, rated input voltage, output with max. rated power	<0.5s	180Vac 50Hz
Output voltage and precision	Ta, rated input voltage, output with rated power	24V±5%	<26V
Output current range	Ta, rated input voltage	0-2.5A	
Output voltage wave	25°C, rated input voltage, output with max. rated power	<600mV	Vp-p
Output overload	25°C, rated input voltage, output with 2 times LED load	YES	--
Output current and precision	Ta, rated input voltage, output with rated power	--	--
Rated output voltage range	Ta, rated input voltage	--	--
Output current wave	25°C, rated input voltage, output with max. rated power	--	Ip-p

·Temperate and others

Item	Conditions	Request	Note
Operation temp.	--	-20-45°C	--
Relative humidity	--	45%-85%	--
Max. case temp.	--	80°C	<90°C
Lifetime	Max.Ta,rated input voltage,output with max.rated power	30,000hr	--
Working noise	25°C, rated input voltage, output with rated power, mute box background noise<35dB, pickup 10cm distance from products	<35dB	--

·Mechanical, mounting

Items	Conditions
Case material and size	Plastic Case 297x30x18mm
Mounting ways	Independent
Insulation type	Class II
IP grade	IP66
Input cables dimension	H05RN-F 2*1.0mm ²
Output cables dimension	SVT 18AWG
Output cables length	Max. 2000mm


·Protection

Items	Conditions	Request	Note
Open circuit	Ta, rated input voltage, no load	--	--
Over load	Ta, 0.94-1.06 times of input voltage, 1.6 times of rated power	yes	--
Short circuit	Ta, 0.94-1.06 times of input voltage	yes	--
Over temperature	Ta, 0.94-1.06 times of input voltage, temperature detected pointed more than 115 degree	yes	--
Over voltage	Ta, 0.94-1.06 times of input voltage,output voltage is 1.5 times of rated one	yes	--
Auto recovery	Over load, short circuit, over heat revocation	yes	--
Latch off	Over voltage re-start after cut off	yes	--

·Standard

Items	Conditions
Safety	IEC61347-1, IEC61347-2-13 (in combination with light IEC60598)
Harmonic	IEC61000-3-2
EMI	IEC55015
EMS	IEC61547

● **Dimensions(mm)**



● **Wiring Diagram**

